

单机延时逃生门锁(DE) Standalone de layegressexit device F451A-DE/F456A-DE

功能说明:

1. 门内①: 工作时压把手语音报警, 延时1-15秒后报警解除, 推把开门
 门内②: 采用主体钥匙复位功能, 解除报警, 推把开门
 门外①: 配置电控把手锁, 需读卡授权释放把手(断电开)开门, 压把手开门
 门外②: 配置机械把手锁, 需钥匙解锁把手, 压把手开门
2. 门锁主体采用12V供电, 断电后主体实现纯机械工作原理
3. 以上功能可适用单门门锁和双门门锁;
4. 可选择单机数显型: BDE
5. 符合: ANSIA156.13-1级
 ANSIA156.25-1级
 UL10C 3小时防火

Function:

1. Interior①: Touch bar more than 2 seconds, the alert is triggered, only after 1-15 seconds (by settings), alarm stop and door can be open.
 Interior②: With key, without any delay and no alarm, door open.
 Exterior①: With electrified trim, authority card to open the door
 Exterior②: With mechanism trim, authority key to open the door
2. Operation voltage: 12V DC
3. Apply to single and double door.
4. Standalone model BDE is available.
5. Compliance to ANSI/BHMA A156.13, A156.25

