


## DLZ08

### 专用房自动开关

#### Automatic switch for special room



外形尺寸: 245mm\*84mm\*14mm  
 工作电压: AC/DC12V~36V  
 工作电流: 待机80mA, 动作160mA  
 显示功能: 灯光显、中英文、盲文、语音提示  
 表面颜色: 银色, 其它色可定制  
 适用区域: 残疾人卫生间 (DWC)、母婴室 (MB)

Size: 245mm\*84mm\*14mm  
 Working voltage: AC/DC12V~36V  
 Current: Standby 80mA, action 160mA  
 Display function: light display, Chinese and English, Braille, voice prompt  
 Surface color: silver, other colors can be customized  
 Applicable area: toilet for the disabled (DWC), mother and baby room (MB)

## DLZ09

### 非接触专用房开关

#### Touchless Special Room Switch



外形尺寸: 282mm\*108mm\*15mm  
 工作电压: AC/DC12V~36V  
 工作电流: 待机110mA, 动作135mA  
 感应距离: 0-7cm  
 显示功能: 灯光显、中英文、盲文、语音提示  
 表面颜色: 金色, 其他色可定制  
 适用区域: 残疾人卫生间 (DWC)、母婴室 (MB)

Size: 282mm\*108mm\*15mm  
 Operating Voltage: AC/DC12V~36V  
 Current: Standby 110mA, action 135mA  
 Induction distance: 0-7cm  
 Display function: light display, Chinese and English, Braille, voice prompt  
 Surface color: gold, other colors can be customized  
 Applicable area: toilet for the disabled (DWC), mother and baby room (MB)

订货型号例 Model example: DLZxx-xxx-xxx

功能描述 Function: DWC残疾人卫生间 Handicapped toilet, MB母婴室 Maternal and child room, FA便利店 The convenience store

## MG01

### 微波感应器

#### Microwave Sensor



外观尺寸: 121mm\*80mm\*51mm  
 最大安装高度: 4000mm, 5000mm可定制  
 安装倾斜度: 0°-90° (纵向) -30°~+30° (横向)  
 电源电压: 12V-24V AC +/-10%  
 工作电流: 静态36mA, 动态73mA

Size: 121mm\*80mm\*51mm  
 Maximum mounting height: 4000mm  
 Install the inclination: 0°~90°, -30°~+30°  
 Working voltage: 12V~24V AC +/-10%  
 Current: 36mA, 73mA

## MG02

### 启动防夹红外线感应器

#### Motion & Presence Infrared Sensor



外观尺寸: 229mm\*67mm\*41mm  
 探测宽度: 800 (W) mm\*1600 (D) mm  
 探测厚度: 800 (W) mm\*1500 (D) mm  
 最大安装高度: 2600mm  
 工作电源: AC/DC12, 24V (-/+10%)  
 工作电流: 静态30mA, 动态110mA  
 导线长度: 2.5m  
 操作指示灯显示: 待机绿色亮, 启动信号黄色, 防夹红色  
 工作温度: -40°C~60°C  
 响应时间: ≤100ms

Size: 229mm\*67mm\*41mm  
 The width of the detection: 800 (W) mm\*1600 (D) mm  
 The thickness of the detection: 800 (W) mm\*1500 (D) mm  
 Maximum mounting height: 2600mm  
 Input volt: AC/DC12, 24V (-/+10%)  
 Current: 30mA, 110mA  
 Wire length: 2.5m  
 Operation indicator light display: standby green bright, start signal yellow, anti clip red  
 Operating temperature: -40~60°C  
 The response time: ≤100ms