

**CE**


## S51D 墙装式防烟电磁门吸

### Wall Mounted Electromagnetic Door Holder

输入电压: DC12V/24V(+10%)  
 工作电流: 12V/80mA 24V/40mA  
 最大拉力: 50kg(100Lbs)直线拉力  
 工作温度: -10~+55°C(14-131F)  
 工作湿度: 0~90%相对湿度  
 防锈处理: 高温烤漆及环保锌电镀处理  
 重 量: 1.0KG  
 外形尺寸: 长80x宽80x厚105(mm)  
 适用场所: 防烟门、通道防火门

Voltage input: DC12V/24V(+10%)  
 Current draw: 12V/80mA 24V/40mA  
 Holding force: up to 50kg  
 Operating temperature: -10~+55°C  
 Operating humidity: 0~95%  
 Finish: power coating or zinc plating  
 Weight: 1.0kg  
 Size: 80mmx80mmx105mm  
 Application region: smoke proof door, fire proof door

**CE**


## S71 墙装式防烟电磁门吸

### Wall Mounted Electromagnetic Door Holder

输入电压: DC12V/24V(+10%)  
 工作电流: 12V/80mA 24V/40mA  
 最大拉力: 50kg(100Lbs)直线拉力  
 工作温度: -10~+55~(14-131F)  
 工作湿度: 0~90%相对湿度  
 防锈处理: 高温烤漆及环保锌电镀处理  
 重 量: 0.90KG  
 外形尺寸: 长70x宽40x高85(mm)  
 适用场所: 防烟门、通道防火门

Voltage input: DC12V/24V(+10%)  
 Current draw: 12V/80mA 24V/40mA  
 Holding force: up to 50kg  
 Operating temperature: -10~+55°C  
 Operating humidity: 0~90%  
 Finish: power coating or zinc plating  
 Weight: 0.9kg  
 Size: 70mmx40mmx85mm  
 Application region: smoke proof door, fire proof door

**CE**


## S71D 墙地两用式防烟电磁门吸

### Electromagnetic Door Holder

输入电压: DC12V/24V(+10%)  
 工作电流: 12V/140mA 24V/50mA  
 最大拉力: 50kg(110Lbs)直线拉力  
 工作温度: -10~+55°C(14-131F)  
 工作湿度: 0~90%相对湿度  
 防锈处理: 不锈钢拉丝, 耐盐雾240小时  
 重 量: 0.90KG  
 外形尺寸: 长118x宽92x高120(mm)  
 适用场所: 防烟门、通道防火门

Voltage input: DC12V/24V(+10%)  
 Current draw: 12V/140mA 24V/50mA  
 Holding force: up to 50kg  
 Operating temperature: -10~+55°C  
 Operating humidity: 0~90%  
 Finish: power coating or zinc plating  
 Weight: 0.9kg  
 Size: 118mmx92mmx120mm  
 Application region: smoke proof door, fire proof door

**CE**


## S72 墙装式防烟电磁门吸

### Wall Mounted Electromagnetic Door Holder

输入电压: DC12V/24V(+10%)  
 工作电流: 12V/180mA 24V/70mA  
 最大拉力: 50kg(110Lbs)直线拉力  
 工作温度: -10~+55°C(14-131F)  
 工作湿度: 0~90%相对湿度  
 防锈处理: 不锈钢拉丝, 耐盐雾240小时  
 重 量: 0.90KG  
 外形尺寸: 长114x宽70x高29(mm)  
 适用场所: 防烟门、通道防火门

Voltage input: DC12V/24V(+10%)  
 Current draw: 12V/180mA 24V/70mA  
 Holding force: up to 50kg  
 Operating temperature: -10~+55°C  
 Operating humidity: 0~90%  
 Finish: power coating or zinc plating  
 Weight: 0.9kg  
 Size: 114mmx70mmx29mm  
 Application region: smoke proof door, fire proof door